

Standard Block Paving




16kg CO₂ per m²

Standard Concrete Block Paving 50mm

A no frills range of standard 200 x 100mm concrete block paving.

- 50mm coloured concrete block paving suitable for driveways, paths or patios
- Robust enough for normal pedestrian and domestic vehicle use
- Standard Block Paving is made in different factories in England, Scotland and Wales therefore variations in colour and tone may occur
- It is recommended that you mix blocks from different packs to minimise shade differences and achieve optimum colour blend
- Joint filling sand and Keybond are recommended (see p.155)

Standard Block Paving	Size mm	No. /m ²	Weight (kg/brick)	No. /pack	Colours	 kg CO ₂ per m ²
	200 x 100 x 50	50	1112	488	BRI, BRA CH, R	16



Brindle (BRI)



Red (R)



Charcoal (CH)



Bracken (BRA)

Remember

The greater part of the cost of ALL driveways will be the installation. Correct preparation, drainage, aggregates, screeding, laying and finishing are essential. Taking any shortcuts in preparation below ground will inevitably lead to early failure of the surface. It may also contravene current planning laws if correct drainage provision has not been made.

Marshalls always recommends employing a qualified installer, preferably one approved from The Marshalls Register (see p.156)

For a more premium look this block size is available in Marshalls Driveline 50 or for a sympathetically aged look, Driveline 50 Vintage, see pages 138-141