



Declaration of Performance

1	Product code	CE 640
2	Product type	Solid Dense Block
3	Intended use	In walls, columns and partitions
4	Company name and contact address	Marshalls Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT
5	Name & contact address of responsible person	N/A
6	System of Assessment & Verification of Constancy of Performance	4
7	Harmonised standard number	EN 771-3:2011+A1: 2015
	Name and identification	
	Performed under	N/A
	Under system	N/A
	And issued	N/A
8	European Technical Assessment	N/A
		N/A
9	Declared Performance	

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions (1)	Length	215mm/440mm	EN 771-3:2011+A1: 2015
	Width	100mm/140mm	
	Height	65mm/215mm	
	Tolerance	D1	
	Shape and features	NPD	
	Group according to BSEN 1996-1-1 (ECG)	Group 1	
Compressive strength (1)	Mean compressive strength	>7.3N/mm ²	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability (1)		<0.6mm/m	
Bond strength (1)	Shear bond strength	0.15N/ mm ² (tabulated value)	BS EN 998-2
	Flexural bond strength	NPD	EN 771-3:2011+A1: 2015
Reaction to fire (2)		A1	Commission Decision 2000/G0S/EC
Water absorption (3)		NPD	EN 771-3:2011+A1: 2015
Water vapour permeability (4)		5/15 (tabulated value)	BS EN 1745: 2012
Direct airborne sound insulation (5) (in end conditions) / [density and configuration]	Gross density	1900Kg/ m ³	EN 771-3:2011+A1: 2015
	Configuration: dimensions and tolerances	Group 1	
Thermal resistance/ [density and configuration] (for units intended to be used in elements subject to thermal insulation requirements)		A0.90W/mK	BS EN 1745: 2012
		1900Kg/m ²	EN 771-3:2011+A1: 2015
		Group 1	
Durability against freeze/thaw		Frost Resistant	BS EN 771-3: 2011 PD 6697
Dangerous substances		NPD	

- (1) for units intended to be used in elements subject to structural requirements
 (2) for units intended to be used in elements subject to fire requirements
 (3) for units intended to be used in damp proof courses or in external elements with exposed face
 (4) for units intended to be used in external elements
 (5) for units to be used in elements subject to acoustic requirements

- 10 The performance of the product identified in Points 1 and 2 is in conformity with the declared performance in Point 9.
The declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Simon Bourne". The signature is fluid and cursive, with a prominent initial 'S'.

Simon Bourne
Group Operations Director

Date: 26th January 2021
Place of Issue: Elland, Halifax, UK