



Declaration of Performance

- 1 **Product code** CE 880
- 2 **Product type** Reconstituted Stone Masonry Unit
- 3 **Intended use** In walls, columns and partitions
- 4 **Company name & contact address** Marshalls Bricks & Masonry
Landscape House,
Lowfields Business Park,
Elland, West Yorkshire HX5 9HT
- 5 **Name & contact address of responsible person** n/a
- 6 **System of Assessment & Verification of Constancy of Performance** 4
- 7 **Harmonised** **BS EN 771-5:2011+A1:2015**
- Name and identification** n/a
- Performed under** n/a
- Under system** n/a
- And issued** n/a
- 8 **European Technical Assessment** n/a

9 **Declared Performance**

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions (1)	Length	<650mm	BS EN 771-5:2011+A1:2015
	Width	<650mm	
	Height	<650mm	
	Tolerance	D1	
	Shape & features	NPD	
	Group according EN 1996-1-1 (EC6)	Group 1	
Compressive strength (1)	Mean Compressive strength	>25N/mm ²	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability (1)		<0.6mm/m	
Bond strength (1)	Shear bond strength	0.15N/mm ² (tabulated Value)	BS EN 998-2
	Flexural bond strength	NPD	BS EN 771-5:2011+A1:2015
Reaction to fire (2)		A1	Commission Decision 2000/605/EC
Water absorption (3)		<3.0g/m ² 50.5	BS EN 771-5:2011+A1:2015
Water vapour permeability (4)		5/15 (Tabulated value)	EN 1745:2012
Direct airborne sound insulation (5)	Gross density	2100Kg/m ³	

(in end conditions) / [Density and configuration]	Configuration; dimensions and tolerances	Group 1	BS EN 771-5:2011+A1:2015
Thermal resistance/ [Density and configuration] (for units intended to be used in elements subject to thermal insulation requirements)		λ 1.11W/mK (dry)	EN 1745:2012
		2100Kg/m ³	BS EN 771-5:2011+A1:2015
		Group 1	
Durability against freeze/thaw		Frost resistant	BS EN 771-5:2011+A1:2015 PD 6697
Dangerous substances		NPD	

- (1) for units intended to be used in elements subject to structural requirements
- (2) for units intended to be used in elements subject to fire requirements
- (3) for units intended to be used in damp proof courses or in external elements with exposed face
- (4) for units intended to be used in external elements
- (5) for units to be used in elements subject to acoustic requirements

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Simon Bourne
Group Operations Director

Date: 26th January 2021
Place of Issue: Elland, Halifax, UK