

Declaration of Performance: CF-144

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

Dry-pressed ceramic tiles with water absorption Eb <0.5%

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

Monowi

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

Modular tiles for internal and external walls and floorings

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

Marshalls, Tile and Stone Interiors, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

Not applicable

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 4

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

BS EN 14411:2012

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

Not applicable

Declaration of Performance: CF-144

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

| Essential Characteristics | Performance | Relevant Clause of BS EN 14411:2012 |
|---------------------------------|--|-------------------------------------|
| Reaction to Fire | Class A1 Without testing (see decision 96/603/EC, as amended) | B.14 |
| Release of dangerous substances | Cadmium NPD | C.3 a) EN 10545-15 |
| | Lead NPD | C.3 b) EN 10545-15 |
| Breaking Strength | >1300N | B-10 a) EN12004 |
| Slip Resistance | R9 | CEN/TS 16165:2012 Annex C |
| Tactility | NPD | B.15 CEN/TS 15209 |
| Durability; | Internal Uses Pass | B.8 EN 10545-12 |
| | External Uses (Freeze-Thaw Resistance) Pass | B.8 EN 10545-12 |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Gemma Jones

Trading Director

Date: 14th February 2018

Version History: Version 2, February 2018 issued due to change in requirements for DOP structure and change of date of issue & director sign off corrected.