

Declaration of Performance: CF-149

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

Modular Tiles of Natural Stone

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

Carrara Nouvo

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

Modular tiles of natural Stone for flooring and stairs, Internal use (see Marshalls brochure for guidance on applications)

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

Not applicable

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 4

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

BS EN 12058:2015

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

Not applicable

Declaration of Performance: CF-149

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

| Essential Characteristics | Performance | Relevant Clause of BS EN 12058:2015 | |
|---|---|-------------------------------------|---------------------------------------|
| Petrographic | Denomination: White with pale greenish and bluish veins, medium to slightly coarse Marble, Turkey | 4.2.2 | |
| Reaction to Fire | Class A1 Without testing (see decision 96/603/EC, as amended) | 4.2.7 | |
| Flexural Strength Expressed as; Lowest Expected Value (LEV) Mean Value and SD | LEV 12MPa | 4.2.4 EN12372 | |
| | Mean 13.3MPa | | |
| | SD 0.4 | | |
| Direct Airborne Sound Insulation | NPD | 4.2.16 EN 1936 | |
| Slip Resistance (mean value) | Wet 10 | Dry 38 | 4.2.13 CEN/TS 1615:2012 Annex C |
| Tactility/Visibility | See description on Brochure/data sheet | 4.2.15 (visual) | |
| Thermal Conductivity (Apparent density kg/m3) | 2624 | 4.2.9 EN 1936 | |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Rory Kendrick

International Stone Sourcing Director

Date: 6th August 2018

Version History: Version 2, August 2018 due to change in requirements to new DoP structure