



CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard BSEN 12058:2004		
Products Natural Stone Products, 15mm Limestone units.		
Denomination Portuguese Limestone Grey to bluish grey, fine to coarse grained, very well compacted fresh Limestone		
Uses Slabs of Natural Stone for flooring and stairs, internal use (see Marshalls Tile and Stone Interiors Natural Stone and Mosaics for guidance on applications)		
Marshalls Tile and Stone Interiors Landscape House Premier Way Lowfields Business Park Elland, West Yorkshire, HX5 9HT United Kingdom	Year of first affixing CE Mark 13	
Aegean Blue Limestone		
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 12058:2004
Reaction to Fire	Class A1 Without testing (see Decision 96/603/EC, as amended)	4.2.7
Flexural strength Expressed as; Lowest Expected Value (LEV) Mean value and SD	LEV (MPa)	5.42
	Mean (MPa)	8.30
	SD	2.83
Slip Resistance (Wet Method)	17	4.2.14 EN 14231
Slip Resistance (Dry Method)	54	4.2.14 EN 14231
Tactility/Visibility	See description on Brochure/data sheet	4.2.15 (Visual)
Thermal Conductivity (Apparent density kg/m ³)	2660-2660	4.2.9 EN 1936

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls Tile and Stone Interiors Natural Stone and Mosaics installation guidelines.

EN 12058:2004

Declaration of Performance

Signed:



Full name: Rory Kendrick

Position: International Natural Stone
Sourcing Director

Date: 18th November 2016