



*Tile and Stone Interiors*

## CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

| <b>Relevant Harmonised Standard</b><br><b>BSEN 12058:2004</b>   |  |                                  |
|---|--|----------------------------------|
| <b>Products</b> Natural Stone Products, 20mm Limestone units.   |  |                                  |
| <b>Denomination</b> <b>French Limestone</b> Pale beige to very pale grey/beige, patches of beige to pale brown, moderately compacted, fresh to locally discoloured (orange/brown) Limestone |  |                                  |
| <b>Uses</b> Slabs of Natural Stone for flooring and stairs, internal use (see Marshalls Tile and Stone Interiors Natural Stone and Mosaics for guidance on applications)                    |  |                                  |
| <b>Marshalls</b><br><b>Tile and Stone Interiors</b><br>Landscape House<br>Premier Way<br>Lowfields Business Park<br>Elland, West Yorkshire, HX5 9HT<br>United Kingdom                       | Year of first affixing CE Mark<br><br>13                                   |                                  |
| <b>Sambonet Limestone</b>   |  |                                  |
| <b>Declared Performance</b>   |  |                                  |
| Essential Characteristics   | Performance Value  | Relevant Clause<br>EN 12058:2004 |
| <b>Reaction to Fire</b>   | <b>Class A1</b><br>Without testing (see Decision<br>96/603/EC, as amended) | 4.2.7                            |
| <b>Flexural strength</b><br>Expressed as; Lowest Expected<br>Value (LEV) Mean value and SD  | LEV (MPa) <b>7.18</b>  | 4.2.4<br>EN 12372                |
|   | Mean (MPa) <b>8.92</b>   |                                  |
|   | SD <b>1.38</b>   |                                  |
| <b>Slip Resistance</b><br>(Wet Method)  | <b>28</b>  | 4.2.14<br>EN 14231               |
| <b>Slip Resistance</b><br>(Dry Method)  | <b>40</b>  | 4.2.14<br>EN 14231               |
| <b>Tactility/Visibility</b>   | See description on Brochure/data<br>sheet                                  | 4.2.15<br>(Visual)               |
| <b>Thermal Conductivity</b><br>(Apparent density kg/m <sup>3</sup> )  | <b>2380 - 2420</b>   | 4.2.9<br>EN 1936                 |

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls Tile and Stone Interiors Natural Stone and Mosaics installation guidelines.

**EN 12058:2004**

## Declaration of Performance

Signed: 

Full name: Rory Kendrick

Position: International Natural Stone  
Sourcing Director

Date: 18<sup>th</sup> November 2016