

1. Unique identification code of the product-type:

This declaration covers sets of plastic drainage channel type M for the collection of superficial waters in pedestrian and vehicular areas with cast iron grating EN 1433,

Drexus Lite	B125 (130x75)
-------------	---------------

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

All packs have batch codes labels for each batch. These are marked on the packaging of the product. Cast iron components POZ90-1351HB Anti-Heel Cast Iron Grating

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Linear drainage systems for trafficked and domestic uses

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshall's, West Lane Works, Southowram, Halifax, West Yorkshire, HX3 9RG

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Attestation Level 3

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

The certifying body Research Institute of Building Materials carried out Initial Type tests, test report no.

**Drainage Channel 409-25 from 25/07/2016
Cast Iron Grating 409-31/1410-1 from 19/12/2016**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance

Essential Requirement	Performance Value		Relevant Clause of BS EN 1433:2002
	Drainage Channel	Cast Iron Grating	
Water Tightness – Jointing of drainage channels	No escape of water noticed	NPD	7.5.1
Load Bearing Capacity, deflection under load Maximum Load	Endured no cracks/no cracks noticed	Endured no cracks/no cracks noticed	7.15
	D400 0,14 / <0,357	B125 0,3 / <2,1	7.16
Permanent Set	NPD	NPD	
Durability	NPD	NPD	6

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 29th July 2021

Group Operation Director

Place of Issue: Elland, Halifax, UK

All EU Declarations from January 2021 will show Version 1 so as to be complimentary with our GB Declaration of Performance.