



Marshalls

CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard BSEN 12058:2015		
Products Natural Stone Products, Granite Paving		
Denomination Pale grey to off white coarse grained fresh granite, hard to very strong		
Uses Modular Tiles of Natural Stone for flooring and stairs, internal use (see Marshalls Internal Stone Brochure for guidance on applications)		
Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT		Year of first affixing CE Mark 15
DoP no.	IS-93	GRA900
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 12058:2015
Reaction to Fire	Class A1 Without testing (see Decision 96/603/EC, as amended)	4.2.7
Flexural strength Expressed as; Lowest Expected Value (LEV) Mean value and SD	LEV	12.1MPa
	Mean	13.1MPa
	SD	0.5
Slip Resistance (sawn surface)	Wet 6	Dry 64
		4.2.13 CEN/TS 16165:2012 Annex C
Direct Airbourne Sound Insulation	NPD	4.2.16 EN 1936
Tactility/Visibility	See description on Brochure/data sheet	4.2.15 (Visual)
Release of Radioactivity	NPD	4.2.18.1

Thermal Conductivity (mean value)	2630kgm3	4.2.17 EN 1745
Release of Dangerous Substances	None	4.2.18.2

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls' installation guidelines.

EN 12058:2015

Declaration of Performance

Signed:



Full name: Rory Kendrick

Position: International Trading Director

Date: 27th October 2015

Document Amended: Corrected
Relevant Clause

Date: 4th February 2016