



Marshalls

CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard BSEN 1343:2012		
Products Kerbs of Natural Stone, Granite from G655 Light Fujian China Uses Domestic/Commercial Kerbstones for external uses (see Marshalls Product Selector brochure for guidance on applications)		
Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT	Year of affixing CE Mark 13	
Thalassa Granite Kerb Off white to pale grey and sporadically very pale pink, coarse grained, fresh granite, very hard to robust		
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 1343:2012
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected value	13MPa	4.4
Freeze/thaw resistance (General) Before and after 56 cycles	14.2/13.2 MPa	4.3.1
Freeze/thaw resistance (De-icing salts)	NPD (no National Annex to this std)	4.3.2
Polishing In use	NPD (no National Annex to this std)	4.6.3
Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products. I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls' installation guidelines. EN 1343:2012		

Declaration of Performance

Signed: 

Full name: Rory Kendrick

Position: International Stone Sourcing
Director

Date: 5th July 2018