

*1. Unique identification code of the product-type:*

**Slabs of Natural Stone, products in this range are pre-blended with each other to formulate 'Kits' of various colours.**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Magnasetts Autumn Gold (50% Aroli Brown / 50% Gaarda)**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving for external uses (see Marshall's brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 1342:2012**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

## Declaration of Performance: ME-136

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance

Essential Characteristics	Performance		Relevant Clause of BS EN 1342:2012
<b>Petrographic</b>	Denomination: Aroli Brown – Brown/red fine grained arenaceous Sandstone from Boondi District, Rajasthan, India.	Denomination: Gaarda Light buff to cream with occasional darker bands Fine grained Sandstone from Boondi District, Rajasthan, India	4.1.1
<b>Release of dangerous substances</b>	NPD	NPD	4.11
<b>Compressive Strength</b> Lowest expected Value	150.57MPa	130.21MPa	4.4
<b>Slip Resistance</b> (wet value)	69 (mean value)	53 (mean value)	4.6.1
<b>Skid Resistance</b>	NPD (mean value)	NPD (mean value)	4.6.2
<b>Freeze/thaw resistance (general)</b> Before and after 56 cycles	36.0/29.1Mpa	35.7/31.9MPa	4.3.1
<b>Freeze/thaw resistance (De-icing salts)</b>	NPD	NPD	4.3.2
<b>Polishing In Use</b>	NPD	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Rory Kendrick

International Stone Sourcing Director

Date: 27<sup>th</sup> September 2018