GB Declaration of Performance: ME-149



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Setts of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Portia Pink Granite Setts

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

GB Declaration of Performance: ME-149



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance		Relevant Clause of BS EN 1342:2012
Petrographic	Denomination: Pink coarse to very grained, very hard and strong Granite from Pontevedra, Spain		4.1.1
Release of dangerous substances	NPD		4.11
Compressive Strength Lowest expected Value	79.33 MPa		4.4
Slip Resistance (wet value)	Shotblast Flamed Honed	71 66 64	4.6.1
Skid Resistance	NPD (mean value)		4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	12.6 /11.8 MPa		4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD		4.3.2
Polishing In Use	NPD		4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

L'mus Sorra

Simon Bourne Group Operation Director Sandburg A report February 2015 and. CLTT 3865 March 2021 Date: 13th December 2021

Place of Issue: Elland, Halifax, UK

Please refer to the data sheet for the design of materials for construction