

## Declaration of Performance: ME-246



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

### **Slabs of Natural Stone**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

### **Lazaro Pearl Step Kit**

3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

### **Slabs of natural Stone for flooring and stairs (see Marshalls brochure for guidance on applications)**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT**

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

### **Not applicable**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

### **System 4**

7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

### **BS EN 12058:2015**

8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

### **Not applicable**

## Declaration of Performance: ME-246



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 12058:2015
Petrographic	Denomination: Cream to pale beige to very pale brown, fine to coarse grained, fresh and well compacted, hard and robust Marble from Turkey	4.2.2
Release of dangerous substances	NPD	4.2.18.2
Flexural Strength Expressed as; Lowest Expected Value (LEV) Mean Value and SD	LEV 11.6MPa Mean 17.1MPa SD 2.8	4.2.4 EN12372
Slip Resistance	Wet 68 Dry 90	4.2.16 CEN/TS 1615:2012 Annex C
Direct Airbourne Sound Insulation	NPD	4.2.16 EN1936
Tactility/Visibility	See description on Brochure/data sheet	4.2.15 (visual)
Release of Radioactivity	NPD	4.2.18.1
Thermal Conductivity	2646kgm3	4.2.18.2

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rory Kendrick

International Stone Sourcing Director

Date: 30<sup>th</sup> May 2018