

*1. Unique identification code of the product-type:*

**Kerbs of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Sargas Granite Kerb**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Kerbstones for external uses (see Marshall's brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 1343:2012**

*8. In case of the declaration of performance concerning a construction product for which a UK Technical Assessment has been issued:*

**Not applicable**

9. Declared performance

| Essential Characteristics                                             | Performance                                                                                                                 | Relevant Clause of BS EN 1343:2012 |
|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| <b>Petrographic</b>                                                   | Denomination: Grey to grey/blue, medium to coarse grained, fresh granite, very well compacted, hard to very hard and robust | 4.1.1                              |
| <b>Release of dangerous substances</b>                                | NPD                                                                                                                         | 4.11                               |
| <b>Flexural Strength</b><br>Lowest expected Value                     | 18.03MPa                                                                                                                    | 4.4                                |
| <b>Freeze/thaw resistance (general)</b><br>Before and after 56 cycles | 20.2/21.5 MPa                                                                                                               | 4.3.1                              |
| <b>Freeze/thaw resistance (De-Icing salts)</b>                        | NPD                                                                                                                         | 4.3.2                              |
| <b>Polishing In Use</b>                                               | NPD                                                                                                                         | 4.6.3                              |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Rory Kendrick

Date: 13<sup>th</sup> January 2021

International Stone Sourcing Director

Place of Issue: Elland, Halifax, UK

Version History: Version 1 January 2021 change to UKCA. B Test Data 25/09/2020.