

*1. Unique identification code of the product-type:*

**Setts of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Farnley Setts – Buff Multi**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 1342:2012**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

9. Declared performance

| Essential Characteristics   | Performance:  |   | Relevant Clause of BS EN 1342:2012 |
|---|---|---|------------------------------------|
| <b>Petrographic</b>   | Denomination: Brown/red fine grained Sandstone. The stone was generally well to very well compacted, with no visible voids and was generally hard to very and strong. | Denomination: Pale Greyish beige to greyish cream with brown red bedding streaks, mainly fine to occasionally medium grained sandstone, well to very well compacted hard to very hard and robust. The stone exhibited a generally faint bedding structure with fine brown red bedding lines. Unevenly distributed brown to red brown spots. | 4.1.1                              |
| <b>Release of dangerous substances</b>                                | NPD   |   | 4.11                               |
| <b>Compressive Strength</b><br>Lowest expected Value                  | 150.57MPa   | 198 MPa   | 4.4                                |
| <b>Slip Resistance</b><br>(wet value)                                 | 69.08 (mean)  | 53 (mean)   | 4.6.1                              |
| <b>Skid Resistance</b>  | NPD   | 64  | 4.6.2                              |
| <b>Freeze/thaw resistance (general)</b><br>Before and after 56 cycles | 37.5/29.1MPa  | 36.3/31.9 MPa   | 4.3.1                              |
| <b>Freeze/thaw resistance (De-Icing salts)</b>                        | NPD   | NPD   | 4.3.2                              |
| <b>Polishing In Use</b>   | NPD   | NPD   | 4.6.3                              |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

**Declaration of Performance: ME-339**

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Rory Kendrick

International Stone Sourcing Director

Date: 12<sup>th</sup> March 2020

Place of Issue: Elland, Halifax, UK