

1. Unique identification code of the product-type:

Setts of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Oberon Granite Setts

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving Setts for external uses (see Marshall's brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

EU Declaration of Performance: ME-354



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1342:2012
Petrographic	Denomination: Light to medium grey, medium coarse grained GRANITE. The stone consisted of interlocking, granular crystals typically measuring 1-2mm across. Dark brown flakes are generally evenly distributed throughout the stone. The stone was very well compacted, hard and strong.	4.1.1
Release of dangerous substances	NPD	4.11
Compressive Strength Lowest expected Value	124MPa	4.4
Slip Resistance (wet value)	Polished	16
	Flamed	75
	Shot Blasted	80
Skid Resistance	NPD (mean value)	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	13.4/14.2 MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Date: 23rd May 2022

Chief Operating Officer

Place of Issue: Elland, Halifax, UK

Sandburg A report July 2020 and Sandburg B Report June 2020

Please refer to the data sheet for the design of materials for construction