



Marshalls

CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard BSEN 1341:2012		
Products Slabs of Natural Stone, Peska, Langvannetand Stillaquarries, Alta municipality, Finnmark county, Norway.		
Uses Domestic/Commercial Paving for external uses (see Marshalls Product Selector brochure for guidance on applications)		
Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT	Year of first affixing CE Mark 13	
Alta Quartzite Paving Grey green, shimmering silver, extremely dense fine to medium grained stone		
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 1341:2012
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected value	29.9MPa	4.4
Slip Resistance (wet value)	63	4.6.1
Skid Resistance Part Polished to BS 7932	NPD Riven or textured surface	4.6.2
Freeze/thaw resistance (General) Before and after 56 cycles	43.7/37.5MPa	4.3.1
Freeze/thaw resistance (De-icing salts)	NPD (no National Annex to this std)	4.3.2
Polishing In use	NPD (no National Annex to this std)	4.6.3

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls' installation guidelines.

EN 1341:2012

Declaration of Performance

Signed:



Full name: Rory Kendrick

Date: 31st March 2015

Position: International Trading Director