

*1. Unique identification code of the product-type:*

**Designed Mortar for Masonry**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Eaglescliffe – M12**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**General Purpose masonry for external elements subject to use in structural applications.**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls Mortars and Screeds Eaglescliffe Plant, Durham Lane, Eaglescliffe, TS16 0PS**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**Attestation Level 2+**

**Certificate Number 0086-CPR-740496**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 998-2:2016**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

## GB Declaration of Performance: MMS MORTAR-03

### 9. Declared performance

Essential Characteristics		Performance	Relevant Clause of BS EN 998-2
Compressive Strength		Minimum Strength of 12.0Nmm <sup>2</sup>	5.4.1 BSEN 998-2:2016
Bond Strength	Sheer Bond	0.15N/mm <sup>2</sup>	5.4.2 BSEN 998-2:2016
	Flexural Bond	NPD	5.4.2.2 BSEN 998-2:2016
Content of Chlorides		0.05%	5.2.2 BSEN 998-2:2016
Reaction to Fire		Class A1	5.6 BSEN 998-2:2016
Water Absorption		0.05kg (m <sup>2</sup> min0.5)	5.4.3 BSEN 998-2:2016
Water Vapour Permeability		μ 15/35	5.4.4 BSEN 998-2:2016
Thermal Conductivity		0.83 W/Mk (tab.Mean Value P=50%)	5.4.6 BSEN 998-2:2016
Durability		Satisfactory	5.4.7 BSEN 998-2:2016


Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

#### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Nick Bebb

Managing Director Marshalls Mortars and Screeds

Date: 9<sup>th</sup> July 2021

Place of Issue: Elland, Halifax, UK