

*1. Unique identification code of the product-type:*

**Slabs of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Moorcroft Natural Stone Paving**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Natural Stone, Cromwell Quarry, Southowram, Halifax, West Yorkshire, HX3 9SZ**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 1341:2012**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

**9. Declared performance**

Essential Characteristics	Performance	Performance	Relevant Clause of BS EN 1341:2012
<b>Petrographic</b>	Denomination: Pale Greenish grey fine grained sandstone, well compacted, generally hard and strong sandstone from Scoutmoor Quarry, Edenfield, Lancashire	Denomination: Pale Grey and pale grey/blue to pale green/grey, mainly fine grained, cross bedded Sandstone from Whitworth Quarry, Whitworth, Greater Manchester	4.1.1
<b>Release of dangerous substances</b>	NPD	NPD	4.11
<b>Flexural Strength</b> Lowest expected Value	22.04MPa	20.9MPa	4.4
<b>Slip Resistance</b> (wet value)	Sawn 78	Sawn 83	4.6.1
<b>Skid Resistance</b>	NPD Riven or textured surface	NPD Riven or textured surface	4.6.2
<b>Freeze/thaw resistance (general)</b> Before and after 56 cycles	26.0/21.9MPa	24.3/20.4MPa	4.3.1
<b>Freeze/thaw resistance (De-icing salts)</b>	NPD	NPD	4.3.2
<b>Polishing In Use</b>	NPD	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Mark Sutherland

Date: 4<sup>th</sup> May 2021

Operations Director-Minerals

Place of Issue: Elland, Halifax, UK A11

Scout Moor A report Sandberg Feb 2012 B report CLTT 3815 14/01/21  
Whitworth A report Sandburg July 2017 report CLTT 3815 14/01/21

Please refer to the data sheet for the design of materials for construction.