

## EU Declaration of Performance: MW-15



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

*1. Unique identification code of the product-type:*

### **Precast Concrete**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

### **Braidwood Blue**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

### **Domestic and Commercial use in Walls, Columns and Partitions**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Roadmeetings, Carluke, South Lanarkshire, ML8 4QG**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

### **Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

### **System 2+**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 771-5:2011+A1:2015**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

### **Not applicable**

## EU Declaration of Performance: MW-15

### 9. Declared performance

Essential Requirement	Performance Value	Relevant Clause within EN 771-5:2011+A1:2015
<b>Dimensions and Dimensional Tolerances</b>	Length +3mm -5mm	5.2.1
	Width +3mm -5mm	5.2.2
	Height +3mm -5mm	
<b>Configuration of units</b>	Solid configuration without voids.	5.3.2
<b>Mean Compressive Strength Homogeneous Category 1 Units. Full Mortar Bed without voids.</b>	41.25 N/mm <sup>2</sup>	5.5.1
<b>Dimensional Stability (Moisture Movement)</b>	0.27 mm/m	5.9
<b>Bond Strength</b>	Shear Bond Characteristic Tested 0.15N/mm <sup>2</sup>	5.12 5.13
	Flexural Bond Parallel Failure >0.26N/mm <sup>2</sup>	
	Mortar Designation iii	
<b>Reaction to Fire</b>	Class A1	5.11
<b>Water Absorption by Capillarity</b>	1g (m2xs)	5.11
<b>Water Vapour Permeability</b>	5/15μ	5.10
<b>Direct Airborne Sound Insulation</b>	Density 2040Kg/m <sup>3</sup> Tolerance category D3	5.4
<b>Thermal Resistance Tabulated values BS EN 772-13</b>	1.07W/mk @ P=50%	5.6
<b>Durability against Freeze Thaw</b>	F1 to EN772-22	5.7
<b>Dangerous Substances</b>	NPD	5.14

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

## EU Declaration of Performance: MW-15



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Simon Bourne".

Simon Bourne

Date: 9<sup>th</sup> June 2021

Group Operation Director

Place of Issue: Elland, Halifax, UK

All EU Declarations from January 2021 will show Version 1 so as to be complimentary with our GB Declaration of Performance.