

*1. Unique identification code of the product-type:*

**Slabs of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Fletcher Bank**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Slabs of natural Stone for flooring and stairs, Internal use**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 12058:2015**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

## Declaration of Performance: SSP-10



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 12058:2015	
<b>Petrographic</b>	Denomination: Light orange/red medium to fine grained Sandstone	4.2.2	
<b>Reaction to Fire</b>	Class A1 Without testing (see decision 96/603/EC, as amended)	4.2.7	
<b>Flexural Strength</b> Expressed as; Lowest Expected Value (LEV) Mean Value and SD	LEV 3.8 MPa	4.2.4 EN12372	
	Mean 6.0MPa		
	SD 1.25		
<b>Slip Resistance</b> (mean value)	Wet 86	Dry 108	4.2.13 CEN/TS 16165:2012 Annex C
<b>Direct Airbourne Sound Insulation</b>	NPD		4.2.16 EN1936
<b>Tactility/Visibility</b>	See description on Brochure/data sheet		4.2.15 (visual)
<b>Release of Radioactivity</b>	NPD		4.2.18.1
<b>Thermal Conductivity</b>	2310 kgm3		4.2.17 EN 1745
<b>Release of dangerous substances</b>	NPD		4.2.18.2

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Andrew Robinson  
Managing Director Mineral Products  
Date: 27<sup>th</sup> April 2018

Version History: Version 2, April 2018 issued due to change in registered trading name.